

## QUICK GUIDE

# Connecting your PTT Voice Responder to Kenwood's Viking Portable Radios



### NOTE!

This guide applies to 18.1 and later VPx000 subscribers and to 19.1 and later VMx000 subscribers.

Your AINA PTT Voice Responder must have manufacturing date 1735 or later to work with Viking Radios. This manufacturing date can be determined by looking at the serial number on the back of the device. For example, with S/N: AW119240215, the manufacturing date is 1924 (year 19, week 24).

## A

## Pairing the AINA PTT Voice Responder to Kenwood's Viking Portable Radios

**Note!** Use Armada to configure specific Bluetooth settings on the radio. Please contact your Kenwood radio dealer for more information.

1. Put your AINA PTT Voice Responder into Kenwood pairing mode by holding Multifunction button while powering it ON:



2. Turn on Bluetooth on your Viking Radio's through its menu options:

Menu	Bluetooth	On / Off	On / Off	On / Off
Bluetooth	1 On / Off	1 Off	1 Off	1 Off
Radio Info	2 Paired Devices	2 On	2 Initializing...	2 On
	3 Scan			
	4 Discoverable			
	EXIT	EXIT	EXIT	EXIT

3. From the same Bluetooth menu opened above, select "Scan", find your PTT Voice Responder from the list (JPTTxxxxxx), and press the "PAIR" button
4. After successful pairing, the PTT Voice Responder's PTT1 button will automatically work. Use Armada to assign/configure the PTT2, Emergency, Left, Right, and Multifunction button if your VPx000 or VMx000 radio is running software version 8.28.x or later (19.2).

**NOTE 1:** The PTT Voice Responder can only be paired to one device at a time.

**NOTE 2:** In the Viking Radio's Bluetooth menu, when you go to the "Recv Audio" menu item, you can select for the audio to be routed to the PTT Voice Responder ("BT Speaker") or radio speaker ("Radio Speaker").

